

Outdoor Freestanding Advertising Kiosks

Sunlight Readable

Brightness is paramount when using outdoor screens these displays use commercial grade Ultra High Brightness panels (3,000 cd/m²), more than 5 times brighter than a standard home TV to allow easy readability in direct sunlight. The display also has an ambient light sensor that will alter the screens brightness based on the displays surrounding light levels. This leave sthe screen with the best clarity while also conserving energy.

Outdoor Enclosure

Designed with robust, corrosion protected, casing to protect against the elements and the public. With an IP65 rating, it keeps out all airborne particles as weel as being protected from any wet weather conditions and also feature waterproof over molded AV connectors. The enclosures are made from mild steel and have thermally toughened glass.

Temperature Control

The internal air-conditioning system allows the screens to be in constant use in an outdoor enrironment. Internal fans keep the panel and other internal components at the optimum working temperature; ensuring a long and reliable life for your display.

Easy Updates

Update the screen via the simple plug and play USB method. You can control the screen from anywhere in the world by

Sturdy Enclosure

Made from mild steel, the enclosure is strong enough to protect the displays components from outside harm such as vandals.

Removable Base

If desired the base can be removed before installation for a more streamline apprearance

Touch Screen Upgrade

An IP65 Rating means the display is able to withstand all weather conditions, wet and dry and also features waterproof over molded HDMI connectors.



Sunlight Readable



24/7Usage

Touch Screen Upgrade



Android Media Player



Vandal Proof



Integrated Temperature S



Network CMS Upgrade

We also offer cloud basis network CMS if required, and you can run the third party Digital Signage software viaour Android PC board too.

e Steel Enclosure



Water Proof

Product Advantages

Outdoor advertising player digital signage Waterproof & Lightning protection LCD display screen kiosk



Product Features



Weather Proofing
Designed for outdoor purpose, all weather proofing!



High Brightness Screen

Screen would get up to 3,000nits as 5 times more than normal display, makes the screen is readable even under the strong sunlight.



Anti-glare Tempered Glass Strong anti-glare tempered glass will ensure passenager would not see the reflected light anytime from any angle.



Lifting Bolt

In the consideration of safety and carry on issue, Screenage put two strong lifting bolt on the tope of the kiosk to avoide this issue.



Security Lock

Double lockes with special & unique keys for the public safety, ensure people can't open that unless they have the right key.



10 Watt Loudspeaker

Two 8 ohm 10 watt outdoor use loudspeaker on the side, ensure passengers could hear what you want they hear.

Specifications

| Model | | | No.622 | | | | | |
|--------------------|--------------------------------------|------------------|---|-----------------|-----------------|-----------------|-----------------|-----------------|
| Panel | Display Size(inch) | | 43" | 49" | 55" | 65" | 75" | 86" |
| | Resolution | | 1920x1080 | 1920x1080 | 1920x1080 | 1920x1080 | 1920x1080 | 1920x1080 |
| | Active Display Area(mm) | | 941.2 x529.4 | 1073.5 x 603.0 | 1209.6 x 680.4 | 1428.5 x 803.5 | 1650.3 x 928.3 | 1938.2 x 1098.3 |
| | Aspect Ratio | | 16:09 | 16:09 | 16:09 | 16:09 | 16:09 | 16:09 |
| | Brightness(cd/m2) | | 3000nit | 3000nit | 3000nit | 3000nit | 3000nit | 3000nit |
| | Contrast Ratio(Typ.) | | 1000:1 | 1000:1 | 1000:1 | 1000:1 | 1000:1 | 1000:1 |
| | Viewing Angle(H/V) | | 178/178 | 178/178 | 178/178 | 178/178 | 178/178 | 178/178 |
| | Color | | 16.7M | 16.7M | 16.7M | 16.7M | 16.7M | 16.7M |
| | Response Time(G-to-G) | | 6ms | 6ms | 6ms | 6ms | 6ms | 6ms |
| | Operation Hour | | 24/7 | 24/7 | 24/7 | 24/7 | 24/7 | 24/7 |
| Sound | Loud Speaker | | 5W, 8Ω (2 sets) | 5W, 8Ω (2 sets) | 5W, 8Ω (2 sets) | 5W, 8Ω (2 sets) | 5W, 8Ω (2 sets) | 5W, 8Ω (2 sets) |
| | Туре | | Internal | Internal | Internal | Internal | Internal | Internal |
| Power | Power Supply | | AC 100 - 240 V~ (+/- 10 %),50/60 Hz | | | | | |
| | Power Consum ption | Max[W/h] | 100 | 120 | 150 | 260 | 280 | 360 |
| | | Sleep mode | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W |
| | | Off mode | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W |
| Mechanical Spec | Protection Glass | | Yes | Yes | Yes | Yes | Yes | Yes |
| | Stand Type | | Foot Stand | Foot Stand | Foot Stand | Foot Stand | Foot Stand | Foot Stand |
| Environmental | Screen Working Temperature | | -10°C ~ 80°C | -10°C ~ 80°C | -10°C ~ 80°C | -10°C ~ 80°C | -10°C ~ 80°C | -10°C ~ 80°C |
| | Operating Environment Temperature | | -10°C ~ 50°C | -10°C ~ 50°C | -10°C ~ 50°C | -10°C ~ 50°C | -10°C ~ 50°C | -10°C ~ 55°C |
| | Operating Humidity | | 10% ~ 80 % | 10% ~ 80 % | 10% ~ 80 % | 10% ~ 80 % | 10% ~ 80 % | 10% ~ 80 % |
| | Storage Humidity | | 5% ~ 95% | 5% ~ 95% | 5% ~ 95% | 5% ~ 95% | 5% ~ 95% | 5% ~ 95% |
| | Cooling System | | Powerful Turbofan & cross flow fan/Air condition (Optional) | | | | | |
| | Hypothermia protection | | Heater (aluminium sheet warmer) (Optional) | | | | | |
| os | | Processor | Rockchip ® 3368 (1.8GHz, octa core) | | | | | |
| | Android Media Player | RAM | 2G | | | | | |
| | | Flash | 8G EMMC | | | | | |
| | | USB | USB2.0 HOST(X2) | | | | | |
| | | LAN | 10M/100M Ethernet(Network version screen only) | | | | | |
| | | External memory | 8GB SD card(up to 32G) | | | | | |
| | | Multimedia | Video(MPG,AVI,MP4,RM,RMVB,TS),Audio(MP3,WMA),Image(JPG,GIF,BMP,PNG) | | | | | |
| | | Media Resolution | 1920*1080 (4K resolution available for some size by request.) | | | | | |
| | | Wi-Fi | 802.11b/g/n Ethernet(Network version screen only) | | | | | |
| | Operating System | | Android 9.0 | | | | | |
| Certifi cation | Safety | | CE ROHS IP65 | | | | | |
| Accessories | Included | | Scheduling software, Remote control, Key, Power cable, SD card | | | | | |
| | Quality assurance | | 1 year (2-3 years optional) | | | | | |
| | Type of packaging | | Carton box /honeycomb box + wooden case | | | | | |





FACTORY



EXHIBITION HALL



WAREHOUSE

COMPANY PROFILE

- Company Name: Screenage Technology
- Established in 2008
- Focus area: Commercial LCD Display Product Development
- 10-Year Professional Manufacturer in Shenzhen, China
- Factory Total Area: 3000m2
- Output: 100,000Pcs/Year
- Product Range: Digital Signge, LCD Video Wall, Floor Standing Kiosk, Industrial LCD Monitor, All-in-one PC and LCD Interactive Whiteboard.
- Main Market: North America, Western Europe, Mid East, Eastern Europe, South America, Africa
- Certificate: ISO9001,CE,EMC,RoHS

Have questions?

We have answers!

Get answers about Pricing, Specifications, Installation, and more

CONTACT US NOW!



E-mail: info@screenage.com